

TANGOTURF F 40

ES3060T

PRODUCT CHARACTERISTICS

PILE HEIGHT	mm	40	+/- 2 mm
TOTAL LENGTH OF TUFT PILE	mm	85	+/- 4 mm
GAUGE		3/4 - 5/8	
PRODUCTION METHOD (DIN 61151)		TUFTED	
STITCH RATE PER M2 APPROX.	nr	10.500	+/- 5 %
TOTAL WEIGHT	gr/m2	1.980	+/- 5 %
PERFORATION DIAMETER	mm	5	+/- 1 mm
NUMBER OF PERFORATIONS	nr/m2	90	
WATER PERMEABILITY (EN12616-REQUIREMENTS>360L/H)		>360 L/H	

YARN CHARACTERISTICS

DECITEX	dtex	9.550	+/- 5 %
COMPOSITION		100% POLYETHYLENE	
THICKNESS	micron	100	+/- 3 %
TYPE		STRAIGHT FIBRILLATED	
COLOUR		GREEN	
TOTAL YARN WEIGHT	gr/m2	870	+/- 5 %

BACKING CHARACTERISTICS

PRIMARY BACKING		POLYPROPYLENE/FLEESE	
PRIMARY BACKING WEIGHT	gr/m2	160	+/- 8 %
BACKING		LATEX	
BACKING WEIGHT	gr/m2	950	+/-10 %

The technical specifications and the quantities of the infillmaterial to be used for the configuration of the "system" must comply with the certificates of the single national and/orinternational Federations or can be requested to our technical office.

Limonta Sport Spa, reserves the right to modify abovespecifications without prior notice in order to update and improve the characteristics of the product in accordance with themost recent deve lopments.

Rev.003 del 29/08/13

